



NEW PRODUCT INFORMATION

INTERNAL DISTRIBUTOR USE ONLY. SPECIFICATIONS AND IMAGES SUBJECT TO CHANGE.

NEW

TOURUS Series

Multiple inputs...with maximum power output

Wharfedale Pro announce a new series of plastic, active loudspeakers delivering power, value and versatility. **Introducing TOURUS.**

Positioned beneath the well established TITAN and the flagship TYPHON series, the new TOURUS series are affordable, powerful and versatile. With a 12" and a 15" version available and with "MBT" models featuring USB mp3 playback and Bluetooth connectivity with TWS stereo link mode, the new series is for anyone needing big power and features on a compact budget.

Custom WP drivers have been selected to ensure that this affordable series have the power and timbre expected from a Wharfedale Pro loudspeaker. In addition, the amplification stages deploy both Class D (LF) and Class AB (HF) to bring power and value to this new series.

With full steel grilles, multiple handles and 4 x M8 rigging points, Tourus is well suited for installations and for hard work on the road.

A new illuminated Wharfedale Pro logo badge is also proudly shown on the front so that Tourus looks as good as it sounds.

450w

Continuous

NEW PLASTIC ACTIVE LOUDSPEAKERS

MULTIPLE INPUTS, BLUETOOTH & USB

CUSTOM WP DRIVERS & RCA INPUTS

TOURUS-AX12 / TOURUS-AX12-MBT

350w Continuous


700w Peak

TOURUS-AX15 / TOURUS-AX15-MBT

450w Continuous

900w Peak

WHAT MAKES THEM GREAT?



- Bi-amplified with Class D and Class AB amps
- Full frontal steel grilles
- 4 x M8 rigging points
- Multiple inputs - 2 channel mixer
- USB mp3, flac & wav playback (MBT models)
- Bluetooth input with stereo link mode (MBT models)
- RCA Stereo inputs

WHEN ARE THEY AVAILABLE?

ORDERS : **SEPTEMBER 2020**

SHIPMENT : **OCTOBER 2020**



NEW PRODUCT INFORMATION


INTERNAL DISTRIBUTOR USE ONLY. SPECIFICATIONS AND IMAGES SUBJECT TO CHANGE.

TOURUS MBT MODELS - UP CLOSE




DIMENSIONS

**TOURUS-AX12
TOURUS-AX12-MBT**




**TOURUS-AX15
TOURUS-AX15-MBT**



TWS BLUETOOTH

Using the BT Stereo link mode, 2 units of TOURUS-MBT create their own Stereo linked pair. TOURUS uses TWS (True Wireless Stereo) technology to create a controllable linked pair of speakers from a single Bluetooth input.



EVERYONE LOVES BASS!

The new T-Sub-AX15B is the perfect active subwoofer partner for a TOURUS. With 700w of Class D Continuous power driving a custom WP 15" Quad layer driver, T-Sub-AX15 is sonically matched for a Wharfedale Pro plastic active speaker.

T-Sub-AX15B with a Tourus, Titan or Typhon brings the low end punch to an active Wharfedale Pro system.

700w
Continuous

T-SUB-AX15B



LED GRILLE



TOURUS not only sounds great- but looks great too! A new, illuminated front grille logo badge adds visual power to the system! Eye catching and cool.

SOFT COVERS

OPTIONAL soft covers are available. Easy to slip on and off, these WP branded covers keep a hardworking TOURUS looking factory fresh!



RCA INPUTS



To allow for easy connection to 'consumer' level devices, TOURUS features standard domestic stereo RCA inputs.

Affordable cabling and consumer grade connectivity allows a TOURUS to be used by almost anyone.



SPECIFICATIONS

NEW

NEW

NEW

NEW



Model Name	TOURUS-AX12	TOURUS-AX12-MBT	TOURUS-AX15	TOURUS-AX15-MBT
System Type	Active 12" 2-way Bi-Amplified	Active 12" 2-way Bi-Amplified	Active 15" 2-way Bi-Amplified	Active 15" 2-way Bi-Amplified
Frequency Response (+/-3dB)	55-20kHz	55-20kHz	50-20kHz	50-20kHz
Sensitivity @ 1w / 1m	96dB	96dB	97dB	97dB
Maximum SPL (peak @1m)	128dB	128dB	130dB	130dB
Low Frequency Transducer				
Size (mm / inches)	305mm / 12"	305mm / 12"	381mm / 15"	381mm / 15"
Coil Size (mm / inches)	50.8mm / 2.0"	50.8mm / 2.0"	50.8mm / 2.0"	50.8mm / 2.0"
Impedance	4Ω	4Ω	4Ω	4Ω
High Frequency Transducer				
Type	Compression Driver	Compression Driver	Compression Driver	Compression Driver
Coil Size (mm / inches)	44.5mm / 1.75"	44.5mm / 1.75"	44.5mm / 1.75"	44.5mm / 1.75"
Exit Size (mm / inches)	25mm / 1"	25mm / 1"	25mm / 1"	25mm / 1"
Diaphragm Material	Titanium	Titanium	Titanium	Titanium
Impedance	8Ω	8Ω	8Ω	8Ω
High Frequency Coverage (H x V)	90° x 60°	90° x 60°	90° x 60°	90° x 60°
Amplifiers				
LF Power Amplifier (Class D)	250w Continuous / 500w Peak	250w Continuous / 500w Peak	350w Continuous / 700w Peak	350w Continuous / 700w Peak
HF Power Amplifier (Class AB)	100w Continuous / 200w Peak	100w Continuous / 200w Peak	100w Continuous / 200w Peak	100w Continuous / 200w Peak
Crossover Frequency	HI PASS 2.5kHz LOW PASS 2.5kHz	HI PASS 2.5kHz LOW PASS 2.5kHz	HI PASS 2.4kHz LOW PASS 2.4kHz	HI PASS 2.4kHz LOW PASS 2.4kHz
Equalization	+/-12dB Gain for bass and treble	+/-12dB Gain for bass and treble	+/-12dB Gain for bass and treble	+/-12dB Gain for bass and treble
Power On Protection	Power switch on / off mute	Power switch on / off mute	Power switch on / off mute	Power switch on / off mute
Thermal Protection	Amplifier shutdown, auto reset	Amplifier shutdown, auto reset	Amplifier shutdown, auto reset	Amplifier shutdown, auto reset
Driver, DC and Short Protection	Yes	Yes	Yes	Yes
Limiter Indicator	Red LED	Red LED	Red LED	Red LED
Power Indicator	Green LED	Green LED	Green LED	Green LED
Input type	Balanced	Balanced / BT / USB	Balanced	Balanced / BT / USB
Input Connectors	2 x TRS JACK, 2 x RCA AND 2 x XLR	2 x TRS JACK, 2 x RCA AND 2 x XLR	2 x TRS JACK, 2 x RCA AND 2 x XLR	2 x TRS JACK, 2 x RCA AND 2 x XLR
Input Impedance	47KΩ Balanced	47KΩ Balanced	47KΩ Balanced	47KΩ Balanced
Maximum Input Level	5V	5V	5V	5V
Line Input Sensitivity	-10dB	-10dB	-10dB	-10dB
Mic Input Sensitivity	-40dB	-40dB	-40dB	-40dB
Line Output Connector	Male XLR	Male XLR	Male XLR	Male XLR
Power Supply	SMPS	SMPS	SMPS	SMPS
AC Power Options	100V-120V and 200V-240V	100V-120V and 200V-240V	100V-120V and 200V-240V	100V-120V and 200V-240V
Power On Indicator	LED / Illuminated front logo	LED / Illuminated front logo	LED / Illuminated front logo	LED / Illuminated front logo
Rigging / Bracket / Mounting Options	4 x M8 35mm Pole-mount with lock screw 3 handles (2 on sides, 1 on top) Optional wall bracket (WPB-2)	4 x M8 35mm Pole-mount with lock screw 3 handles (2 on sides, 1 on top) Optional wall bracket (WPB-2)	4 x M8 35mm Pole-mount with lock screw 3 handles (2 on sides, 1 on top) Optional wall bracket (WPB-2)	4 x M8 35mm Pole-mount with lock screw 3 handles (2 on sides, 1 on top) Optional wall bracket (WPB-2)
Enclosure				
Enclosure Material	Injection Moulded Polypropylene	Injection Moulded Polypropylene	Injection Moulded Polypropylene	Injection Moulded Polypropylene
Colour	Black	Black	Black	Black
Grille	1.2mm steel	1.2mm steel	1.2mm steel	1.2mm steel
Dimensions (Unpacked)				
Height	603mm / 23.7"	603mm / 23.7"	693mm / 27.3"	693mm / 27.3"
Width - Front	377mm / 14.8"	377mm / 14.8"	455mm / 17.9"	455mm / 17.9"
Width - Rear	217mm / 8.54"	217mm / 8.54"	262mm / 10.3"	262mm / 10.3"
Depth	347mm / 13.7"	347mm / 13.7"	401.8m / 15.1"	401.8m / 15.1"
Dimensions (packed)				
Height	666mm / 26.2"	666mm / 26.2"	762mm / 30.0"	762mm / 30.0"
Width	430mm / 16.9"	430mm / 16.9"	508mm / 20.0"	508mm / 20.0"
Depth	408mm / 16.1"	408mm / 16.1"	425mm / 16.7"	425mm / 16.7"
Weight				
Net Weight (kg / lbs)	15.0kg / 33.0lbs	15.0kg / 33.0lbs	19.2kg / 42.2lbs	19.2kg / 42.2lbs
Gross Weight (kg / lbs)	17.0kg / 37.4lbs	17.0kg / 37.4lbs	22.0kg / 48.4lbs	22.0kg / 48.4lbs

Errors and omissions excepted (E&OE) : Wharfedale Pro : 2020



WWW.WHARFEDALEPRO.COM